

## TMU MINITRUNKING WITH OVERLAPPING COVER

### PRODUCT TYPE:

Trunking system for cables and outlet boxes in plastic material

### APPLICATIONS:

Wall and/or ceiling trunking



PRODUCT RANGE:	BASES		HEIGHT	
		10		17
<i>Dimensions in mm</i>	15			X
	22	X		
	25			X
	30	X (1 or 2 compartments)		
	40			X (2 compartments)

### COLOUR RANGE:

White RAL 9001

### MATERIAL:

PVC

### DECLARATION OF CONFORMITY:

All TMU range products come under the scope of the Low Voltage Directive 2014/35/UE and comply with all relevant essential requirements set in the Directive.

Compliance with the Directive is indicated by the **CE** marking and by all required symbols and markings affixed on the product, its packaging, in the assembly instructions and product catalogue, as well as by full product compliance with applicable standards.

### NORMATIVE REFERENCES:

- EN 50085-1: "Cable trunking systems and cable ducting systems for electrical installations – Part 1: General requirements"
- EN 50085-2-1: "Cable trunking systems and cable ducting systems for electrical installations – Part 2-1: Cable trunking systems and cable ducting systems intended for mounting on walls and ceilings"

**Degree of Protection Provided by Enclosures** as per Standard EN 60529 "Degrees of Protection Provided by Enclosures (IP Code)": IP40

**Resistance to impact** for installation and application (EN 50085-1 par. 6.2): 2 Joules



**MINIMUM STORAGE  
AND TRANSPORT  
TEMPERATURE:** -15 °C

**MINIMUM INSTALLATION  
AND SERVICE  
TEMPERATURE:** +15 °C

**MAXIMUM SERVICE  
TEMPERATURE:** +60 °C

**FLAME PROPAGATION  
RESISTANCE  
ACCORDING TO  
EN 60695-11-2  
STANDARD:** non-flame propagating  
(1KW PRE-MIXED TEST FLAME)

**SELF-EXTINGUISHING  
MATERIAL ACCORDING  
TO UL94 STANDARD:** V0

**ELECTRICAL INSULATING  
PROPERTIES:** yes (rated voltage up to 1000 V AC)

**MECHANICAL  
STRENGTH:** the covers can be removed only with a tool

**RESISTANCE TO IMPACT  
AS PER EN 62262  
STANDARD :** "Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts (IK Code)": IK07 (2 Joules)

RESISTANCE TO CHEMICAL AGENTS:	Saline	Acids		Bases		Solvents				Mineral Oil
		Concentrated	Thinned	Concentrated	Thinned	Hexane	Benzoic acid	Acetone	Ethyl-alcohol	
	Resistant	Resistant in certain conditions	Resistant	Resistant in certain conditions	Resistant	Resistant	Unsuitable	Unsuitable	Resistant	Resistant

**OTHER FEATURES:**

- Full range of components and accessories
- Outlet boxes in compliance with all major European standards
- Components are snap-mounted on the trunking base

**MARKINGS  
AND CERTIFICATIONS:** 

**CONFORMITY WITH  
2011/65/CE (ROHS)  
DIRECTIVE:** yes

